



REV	DESCRIPTION	DATE

**NOTES**

Available in 06 through 80 Circuits  
 Material: PBT UL94V-0  
 Contact Material: Phosphor Bronze  
 Flat Ribbon Cable With 0.635mm Pitch

**SPECIFICATION:**

Current rating: 0.5 Amp.  
 Contact Resistance: 30mΩ Max.  
 Insulation Resistance: 1000MΩ Min.  
 Operating Temperature Range: -40°C ~ +105°C

**ORDERING INFORMATION**

**YY - 4651 - XX G P W**  
                                   **1 2 3 4**

- No. of Circuits 06~80
- Plated  
     G : Gold Plating
- P : Phosphor Bronze
- W : W/ Lock

No.	A	B	C	No.	A	B	C	No.	A	B	C
06	8.01	2.54	2.54	22	18.17	12.70	12.70	40	29.60	24.13	24.13
08	9.28	3.81	3.81	24	19.44	13.97	13.97	44	32.14	26.67	26.67
10	10.55	5.08	5.08	26	20.71	15.24	15.24	50	35.95	30.48	30.48
12	11.82	6.35	6.35	30	23.25	17.78	17.78	60	42.30	36.83	36.83
14	13.09	7.62	7.62	32	24.52	19.05	19.05	64	44.84	39.37	39.37
16	14.36	8.89	8.89	34	25.79	20.32	20.32	68	47.38	41.91	41.91
20	16.90	11.43	11.43	36	27.06	21.59	21.59	80	55.00	49.53	49.53



<b>TOLERANCE</b>		 <b>Young Yak Enterprise Co., Ltd.</b>				
X.	--				<b>TITLE</b> 1.27mm(.050") Pitch IDC Socketer	
X.X	±0.35					
X.XX	±0.25					
X.XXX	±0.10					
ANGULAR	--					
<b>APPROVALS</b>						
DRAWN	Kang	VIEW	SCALE	PART NO.	REV.	
	29-October-2013		F	YY-4651-XXGPW	A0	
CHECKED	Denise	UNIT	SIZE	DWG NO.	SHEET	
	29-October-2013	MM	A4	YY-4651-XXGPW-143	1 OF 1	
APPROVED	Jessica					
	29-October-2013					