




INTRODUCTION

YY-1850 and YY-1870 series is pitch 2.00mm and available in 2- to 40-circuit. It's single row.

This series is wire to board connector including receptacle housings, female terminals and straight/ right angle pin header and surface mount header.

- Terminal is with gold flash plating
- It accepts AWG #26 ~ #30 wire range
- Headers are unshrouded and with both surface mount and through-hole type.
- Pin is 0.64mm square pin. Different pin length is under requested

Connector Systems Table of Contents 2.00 mm(.079") Pitch Wire To Board Connectors



SPECIFICATION

- Rated current : 3A Max.
- Rated voltage : 250 V AC
- Contact resistance : 20 mΩ Max.
- Insulation resistance : 1, 000 MΩ Min.
- Dielectric withstand voltage : 800V AC / minute
- Temperature range : -25 °C / +85 °C
- Packaging : Header - Bag
Housing - Bag
Terminals - Reel

CONSUMER

Automotive

- Interior lighting
- Stereos
- Window defrosters

Consumer

- Coin changers
- Fire alarms / smoke detectors
- Gaming equipment
- Garage doors
- Home Security
- Home appliances
- Slot machines

Data/Communications

- Copiers
- Mainframe Computers
- Multi-function scanners
- Workstations